



Product Service

Compliance Document

No. D 083373 0064 Rev. 00

Holder of Certificate: **JIANGSU GOODWE POWER SUPPLY TECHNOLOGY CO., LTD.**

No. 90 Zijin Road
New District
215011 Suzhou
PEOPLE'S REPUBLIC OF CHINA

Product: **Converter
AC coupled energy inverter with storage
battery system**

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. For details see: www.tuvsud.com/ps-cert

Test report no.: 704092001916-00

Date, 2020-09-29

(Zhengdong Ma)

Compliance Document

No. D 083373 0064 Rev. 00

Model(s): AC coupled energy inverter: GW5000S-BP, GW3600S-BP

Storage battery system: BYD: LVS4.0, LVS8.0, LVS12.0, LVS16.0, LVS20.0, LVS24.0

Parameters:

AC coupled energy inverter with storage battery system:		
1) Storage battery system parameters:		
Battery Type	Li-ion	
Model	Manufacturer	Piece(s) of battery module recommended
LVS4.0	BYD	1
LVS8.0	BYD	1
LVS12.0	BYD	1
LVS16.0	BYD	1
LVS20.0	BYD	1
LVS24.0	BYD	1
BMS firmware version	V1.8	
2) Hybrid inverter parameters:		
Inverter model name	GW5000S-BP, GW3600S-BP	
a) Battery input:		
Battery voltage range	d.c. 40-60V	
Nominal battery voltage	d.c. 48V	
Max. charge/discharge current	d.c. 75A/75A (GW3600S-BP) d.c. 100A/100A (GW5000S-BP)	
b) AC-output (grid side):		
Rated output voltage	a.c. 230V	
Rated output frequency	50Hz	
Rated output power	3680W (GW3600S-BP) 5000W (GW5000S-BP)	
Max. apparent output power	4050VA (GW3600S-BP) 5100VA (GW5000S-BP)	
Max. output current	a.c. 16A (GW3600S-BP) a.c. 22.8 (GW5000S-BP)	
Displacement factor	-0.9...1...+0.9	

Compliance Document

No. D 083373 0064 Rev. 00

AC coupled energy inverter with storage battery system:	
c) AC-output (back-up):	
Rated output voltage	a.c. 230V
Rated output frequency	50Hz
Rated output power	3680W (GW3600S-BP) 5000W (GW5000S-BP)
Rated output current	a.c. 16A (GW3600S-BP) a.c. 21.7A (GW5000S-BP)
d) AC-input	
Rated voltage	a.c. 230V
Rated output frequency	50Hz
Current (Maximum continuous)	a.c. 32A (GW3600S-BP) a.c. 40A (GW5000S-BP)
e) Other parameters:	
Protection class:	I
Degree of protection:	IP65
Overvoltage category:	II (PV), III (MAINS)
Ambient temperature:	-25°C...+60°C
Firmware version	0707A

DISPOSITIVO DI INTERFACCIA Interface Device	PROTEZIONE DI INTERFACCIA Interface Protection Device	DISPOSITIVO DI CONVERSIONE STATICA Static Conversion Device	DISPOSITIVO DI GENERAZIONE TOTANTE Rotating Device
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Tested according to:

CEI 0-21:2019